



PROCEEDINGS OF 14th INTERNATIONAL MINERAL PROCESSING SYMPOSIUM

October 15 - 17, 2014

Kuşadası – Turkey

Mineral Processing in Everything!

Editors

Üner İPEKOĞLU, Vedat ARSLAN and Sezai ŞEN

Dokuz Eylül University, Department of Mining Engineering



Turkish Mining Development Foundation

Kuşadası - Turkey

October 15 - 17, 2014

Website: www.imps2014.org

The proceedings are also available in USB flash memory.

Publisher : Turkish Mining Development Foundation

ISBN : 978-975-441-436-3

Edited by : Üner İPEKOĞLU, Vedat ARSLAN, Sezai ŞEN

Printing Layout : Sezai ŞEN, Baran TUFAN

Published by : Üç Adım Matbaa-Reklam Ltd. Şti. Izmir/Turkey

*The Proceedings of 14th International Mineral Symposium was printed by
the contribution of TUBITAK.*

ORGANIZING COMMITTEE

Symposium Presidents

Dr. Nevzat KAVAKLI

Deputy Undersecretary, Ministry of Energy & Natural Resources

Mustafa AKTAŞ

General Director of The Turkish Coal Enterprises

Symposium Chair

Prof. Dr. Üner İPEKOĞLU

Dokuz Eylül University

Institutional Advisory Committee (in alphabetical order)

Ayhan YÜKSEL

President, Chamber of Mining Engineers of Turkey

Burhan İNAN

G. Director of The Turkish Hard Coal Enterprises

Prof. Dr. Ercüment YALÇIN

Dean, Faculty of Eng., Dokuz Eylül University

Prof. Dr. Güven ÖNAL

President, Turkish Mining Development Foundation

Prof. Dr. Mehmet FÜZÜN

Rector, Dokuz Eylül University

Mehmet Hamdi YILDIRIM

G. Director of The Mining Affairs

M. Ümit AKDUR

Turkish Gold Miners Association

Mehmet ÜZER

G. Director, Mineral Res. & Expl.

Dr. Orhan YILMAZ

General Manager, Eti Mine Works

Prof. Dr. Turan BATAR

President, Mineral Processing Society of Turkey

Industrial Advisory Committee (in alphabetical order)

Ahmet TEZCAN

Eti Copper Inc.

Alp GÜRKAN

Soma Coal Inc.

Arif KURTEL

İmbat Mining Inc

Bülent TÜFEKÇİOĞLU

Tüfekçioğlu Rubber, Mac. and Min. Ind. Co.

David A. BICKFORD

Tüprag Metal Mining Industry & Trade

Ergun TUNCER

Bilfer Mining Inc.

İsmet SİVRİOĞLU

Koza Gold Operations Company

Jeremy SHORT

Anagold Mining Inc.

Murat Zekeriya AYDIN

Kolin Construction

Oktay Rıfat KUŞOĞLU

Coal Enterprises Inc.

Özlem ÖNAL

Dedeman Mining

Sabri KARAHAN

DAMA Engineering Co.

Savaş ŞAHİN

Demir Export Inc.

Serdar NİŞLİ

Aksa Enerji

Şeyda ÇAĞLAYAN

Türk Maadin Inc.

STEERING COMMITTEE

Prof. Dr. A. Üner İPEKOĞLU
Prof. Dr. Hüseyin ÖZDAĞ
Prof. Dr. Güven ÖNAL
Prof. Dr. Ümit ATALAY
Prof. Dr. Gülhan ÖZBAYOĞLU
Prof. Dr. Özcan GÜLSOY
Prof. Dr. Çetin HOŞTEN
Prof. Dr. Levent ERGÜN
Prof. Dr. A. İhsan AROL
Prof. Dr. Volkan BOZKURT
Prof. Dr. Gündüz ATEŞOK
Prof. Dr. Neşet ACARKAN

HONORARY MEMBERS

Prof. Dr. M. Zeki DOĞAN
Prof. Dr. Ali AKAR
Dr. H. Avni YAZAN
Prof. Dr. Yaşar ÇILINGİR
Prof. Dr. Suna ATAK
Prof. Dr. Halim DEMIREL
Prof. Dr. Erdoğan YİĞİT
Prof. Dr. İrfan BAYRAKTAR
Prof. Dr. Mevlüt KEMAL
Prof. Dr. Mehmet CANBAZOĞLU
Sabri KARAHAN

LOCAL COMMITTEE (*Dokuz Eylül University*)

Prof. Dr. Vedat ARSLAN
Prof. Dr. İlknur CÖCEN
Prof. Dr. Erol KAYA
Prof. Dr. Mehmet TANRIVERDİ
Assoc. Prof. Dr. Tayfun ÇİÇEK
Assoc. Prof. Dr. Abdullah SEYRANKAYA
Assoc. Prof. Dr. Ufuk MALAYOĞLU
Assoc. Prof. Dr. Sezai ŞEN
Assist. Prof. Dr. Hatice YILMAZ
Lecturer Dr. Özge GÖK
Lecturer Dr. Baran TUFAN
Resc. Assist. Dr. Erkan GÜLER
Resc. Assist. Dr. Gül Akar ŞEN
Resc. Assist. Dr. Vedat Taylan ENGİN
Resc. Assist. Ebru TUFAN
Resc. Assist. Çağrı ÇERİK
Resc. Assist. Ümit HORASAN

THE OPTIMIZATION AND THE PRECONDITION FOR INCREASING OF GOLD RECOVERIES FROM DOMESTIC MINES

Boris Krstev^{1,a} and Aleksandar Krstev²

¹Goce Delcev University, Faculty of Natural & Technical Sciences, 2000 Stip, The Republic of Macedonia

²Goce Delcev University, Faculty of Computer Sciences, 2000 Stip, The Republic of Macedonia,

a. Corresponding author (boris.krstev@ugd.edu.mk)

ABSTRACT

The increasing in the chalcopyrite copper Bucim mine are gone forward to renewed reagent regime, including and involving new reagents for increase d recovery of copper and gold. The optimization and mathematical linear are good example for improvement of industrial recoveries in flotation circuit. Nevertheless, the choice between flotation and new leaching or bioleaching method are challenge for future. The optimization techniques, formating the mathematical model and adequate model for carried out investigations, by means of tables and figures will show the optimal quantity in reagent regime (collectors), particle size, flotation time, rougher flotation, conditioning time etc.

1.General principles

The previous carried out laboratory investigations with application of the new collectors and frothers confirmed that there is possibility for significantly improvement of the gold recovery with same copper quality and decreasing of the CaO consumption. The investigations with reagents Aerophine 3404, Aero XD 5002 and frother OP-F49 in the previous period (2010/11) were very short because of the low quality and variations of the ores. Variations of the ore from 0.15-0.22%Cu, instability of the flotation and other problems in the flotation process. The combination of the Aerophine 3404, KEX:KBX= 1:1, NaIPX, SKIK- Bz 2000, in the different points of the flotation process gave significantly better results than early. The process was prolonged with pH=10.5 and the point of addition of CaO was at the hydro cyclone (70%) and 30% in the flotation process. The conclusions of these investigations were very heavy for sure confirmation, bur the obtained results were close to the previous results by standard conditions (specially for Au), may be better but not significantly. The Au content in the ore was on 0,19-0,29 gr/t, in the concentrate

8-12,3 gr/t, with Au recovery from 45-55% (some appearances up to 60%), but the copper recovery in the standard interval. Considering these investigations in laboratory and industrial real conditions may be concluded that:

- The instability and relative short period of investigations in the real conditions have contributed for obtaining the technological parameters closed to the standard conditions,
- As a result of the good regrounding, it was very heavy to clean the rough concentrate Cu/Au,
- Using higher pH, higher than standard in the rougher flotation (elimination of pyrite flotation) by Aerophine 3404, it will be expected higher quality and content of Cu/Au,
- In the existing real conditions of flotation at pH 11,0-11,6 and consumption of Aerophine 3404

- (AP3404) from 18-22 gr/t, together with change of adaptive changeable reagent regime by different collectors (the combination from Aerophine 3404, KEX:KBX, NaIPX),
- The prolonged changes of the reagent regime with contemporary addition of new reagents (Bz 2000 = 4-8 gr/t + KEX:KBX=1:1 = 8-4 gr/t, total 12 gr/t) in the grinding cycle, together with addition of NaIPX in the condioner with 8-10 gr/t, in the flotation process (rougher and controlled flotation) with 2-4 gr/t, or total addition of 14 gr/t NaIPX

The tests A1-A16 are related to the ore grindibility in the presence of the BZ2000 (7 gr/t), conditioning time (6 min.) with BZ2000 (5 gr/t) + DowF (10 gr/t) after 4 min., rougher flotation (4 min.), and scavenging flotation (4+4 minutes) (NaIPX 6+4 gr/t + DowF 5+5 gr/t). The tests A7-A8 are related for the ore grinding in the presence of the KEX:KBX= 8 gr/t, conditioning time of (6 min.) with BZ2000 (4 gr/t) + DowF (10 gr/t) after 4 minutes, rougher flotation (4 min.), and scavenging flotation (4+4 minutes) (NaIPX 8+4 gr/t + DowF 5+5 gr/t). The tests A11-A16 are related for the grinding ore in the presence of KEX:KBX= 6 gr/t, conditioning time of (6 min.) with KEX:KBX= (4 gr/t) + DowF (10 gr/t) after 4 minutes, rougher flotation (4 min.), and scavenging flotation (4+4 minutes) (NaIPX 8+4 gr/t + DowF 5+5 gr/t). and variants with condition 6 minutes with BZ2000 (4 gr/t) + dispersgator (50 gr/t), or variant with BZ2000 in all existing phases: conditioning, rougher and control flotation.

Table 1. Investigated conditions for flotation for gold - plan

Tests	Collectors, typ	Coll., gr/t	pH
A-1	BZ 000+Naikol+NaIPX	22	11.75
A-2	BZ 000+Naikol+NaIPX	22	11.75
A-3	KEX:KBX +NaIPX	18	11.75
A-4	KEX:KBX + NaIPX	18	11.75
A-5	KEX:KBX +NaIPX	22	11.80
A-6	KEX:KBX + NaIPX	22	11.80
A-7	KEX:KBX+BZ 2000+NaIPX	22	11.80
A-8	KEX:KBX+BZ 2000+NaIPX	22	11.80
A-9	Naikol+NaIPX	22	10.60
A-10	Naikol+NaIPX	22	10.60
A-11	KEX:KBX + Naikol	22	11.80
A-12	KEX:KBX + Naikol	22	11.80
A-13	KEX:KBX + NaIPX	16	11.80
A-14	KEX:KBX + NaIPX	16	11.80
A-15	KAX + NaIPX	22	11.80
A-16	KAX + Naikol + NaIPX	22	11.80

Table 2. Tests with a plan experiments on gold

Tests	Content, (k ,r, j), Au(gr/t)			Recovery (K,J), Au(gr/t)	
	k	r	j	K	J
A-1	5.700	0.281	0.170	40.63	59.37
A-2	4.200	0.279	0.170	40.67	59.33
A-3	4.800	0.278	0.160	43.98	56.02
A-4	5.200	0.264	0.150	44.38	55.62
A-5	5.500	0.320	0.110	66.99	33.01
A-6	5.800	0.390	0.120	70.68	29.32
A-7	4.300	0.308	0.100	69.13	30.87
A-8	4.200	0.261	0.090	66.89	33.11
A-9	4.000	0.303	0.100	68.69	31.31
A-10	4.000	0.339	0.120	66.62	33.38
A-11	3.600	0.269	0.110	60.94	39.06
A-12	4.200	0.272	0.110	61.09	38.91
A-13	4.900	0.335	0.120	65.80	34.20
A-14	5.100	0.391	0.130	68.49	31.51
A-15	3.400	0.165	0.025	85.48	14.52
A-16	3.700	0.242	0.050	80.39	19.61

The tests A1-A16 are carried out in the different conditions and different reagent regime and collectors, conditioning, rougher and control flotation with the reagent regime shown at the tables.

Table 3. Tests with a plan experiments on gold 2012/13

Tests	Content, (k ,r), Au (ppm)	Recovery (K,J), Au (%)	
T - 1	1.40	0.26	56.1
T - 2	1.49	0.29	49.8
O-1	2.20	0.22	38.83
O-2	2.45	0.24	44.20
O-3	1.95	0.23	46.60
O-4	2.50	0.19	33.46
O-5	2.80	0.18	40.07
O-6	2.25	0.20	34.60
O-7	1.90	0.23	51.05
O-8	2.45	0.20	42.06
O-9	1.95	0.19	36.54
O-10	2.75	0.21	35.11
			64.89

Table 4. Tests with a plan experiments on gold 2012/13

Tests	Content, (k ,r), Au (ppm)	Recovery (K,J), Au (%)	
T - 1	1.40	0.26	56.1
T - 2	1.49	0.29	49.8
O'-1	1.56	0.19	39.91
O'-2	1.49	0.25	58.52
O'-3	1.47	0.22	48.58
O'-4	1.49	0.23	52.03
O'-5	1.55	0.24	52.13
O'-6	1.78	0.20	40.33
O'-7	2.55	0.17	30.86
O'-8	2.15	0.19	39.01
O'-9	2.15	0.20	31.77
O'-10	1.95	0.19	33.82
			66.18

3.RESULTS AND DISCUSSION

According to the previous investigations and obtained results from these investigations and tests for the Bucim mine ores, these particular investigation are carried out by means of experiment plans, laboratory investigations etc. These investigations show advanced approach for eventual optimization of the flotation process from useful raw material or chalcopyrite ores with possibility of obtaining the optimal results.

4. CONCLUSION

In this paper is shown practical applicative optimization techniques with formatting the model for adequate reagent regime for carried out investigations. Obtained tabular results will show the optimal quantity in reagent regime (collectors), particle size, flotation time for rougher flotation, conditioning time, some addition of special reagents etc.

REFERENCES

- Mular, A. L., (1980). "Empirical modeling and optimisation of mineral processes", Mineral Science and Engineering, 4, No 3. Pp 30-42.
- Napier-Munn, T. J., Morrell, S., Morrison, R. D., and Kojovic, T., (1996). "Mineral comminution circuits: their operation and optimization". JKMRCC, pp. 413.
- Plitt, L. R., (December, 1976). "A mathematical model of the hydrocyclone classifier", CIM Bull. 69, 114.
- Povarov A. I., (1978). "Hydrocyclones in Mineral Processing", "Nedra". Moskva, Russia.
- Renner, V. G., and Cohen, H. E., (June, 1978). "Measurement and interpretation of size distribution of particles within a hydrocyclone", Trans. IMM, Sec. C, 87, 139.
- Rowland C. A., (1986). "Ball Mill Scale-up-Diameter Factors., Advances in Mineral Processing", P. Somasundaram Editor Society of Mining Engineers/AIME, 34, 605.
- Svarovsky, L., (1984). "Hydrocyclones", Holt, Rinehart & Winston Ltd, Eastbourne.
- Wiegel R. L., and Li K. A., (1986). "Random Model for Mineral Liberation by Size Reduction", Trans. AIME, 238, 179.
- Wills, B. A. (1988). "Mineral Processing Technology", 4th edition
- A.Krstev,(2012), PhD Thesis, 2012 UGD-Stip, Macedonia