

XIV INTERNATIONAL SCIENTIFIC CONGRESS
SUMMER SESSION

MACHINES. TECHNOLOGIES. MATERIALS 2017



PROCEEDINGS

YEAR I. ISSUE 5 (5)

VOL. V
MACHINES.
ERGONOMY & DESIGN

ISSN 2535-0021 (Print)

ISSN 2535-003X (Online)

ORGANIZER

SCIENTIFIC-TECHNICAL UNION OF MECHANICAL ENGINEERING - INDUSTRY 4.0
BULGARIA

The FEDERATION OF THE SCIENTIFIC ENGINEERING UNIONS (FSEU)

In Bulgaria is a professional, scientific - educational, non-governmental, non-political non-profit association of legal entities - professional organizations registered under the Law on non-profit legal entities, whose members are engineers, economists and other specialists in the field of science, technology, economy and agriculture.

FSEU performed bilateral cooperation with similar organizations from many countries.

FSEU brings together 19 national associations - Scientific and Technical Unions / STU /, 34 territorial associations, which have more than 15 000 professionals across the country.

FSEU is a co-founder and member of the World Federation of Engineering Organizations (WFEO).

FSEU a member of the European Federation of National Engineering Associations (FEANI), and a member of the Standing Conference of engineering organizations from Southeast Europe / CO.PICEE /, Global Compact, European Young Engineers (EYE). The Federation has the exclusive right to give nominations for the European Engineer (EUR ING) title.

Contacts:

108 Rakovsky Str., Sofia 1000, Bulgaria

web: www.fnts.bg

e-mail: info@fnts.bg

**INTERNATIONAL SCIENTIFIC CONGRESS
MACHINES. TECHNOLOGIES. MATERIALS**

13-16.09.2017, VARNA, BULGARIA

PROCEEDINGS

YEAR I, ISSUE 5 (5), Varna, Bulgaria 2017

VOLUME V "MACHINES, ERGONOMICS & DESIGN"

**ISSN 2535-0021 (PRINT)
ISSN 2535-003X (ONLINE)**

PUBLISHER:

**SCIENTIFIC TECHNICAL UNION OF MECHANICAL
ENGINEERING
INDUSTRY 4.0**

**108, Rakovski Str., 1000 Sofia, Bulgaria
tel. (+359 2) 987 72 90,
tel/fax (+359 2) 986 22 40,
office@mitcongress.com
www.mitcongress.com**

INTERNATIONAL EDITORIAL BOARD

Chairman: Prof. DHC Georgi Popov

Members:

Acad. Ivan Vedyakov
Acad. Yurii Kuznetsov
Prof. Aleksander Mihaylov
Prof. Anatoliy Kostin
Prof. Adel Mahmud
Prof. Ahmet Ertas
Prof. Andrzej Golabczak
Prof. Boncho Bonev
Prof. Gennady Bagluk
Prof. Detlef Redlich
Prof. Dipten Misra
Prof. Dmitry Kaputkin
Prof. Eugene Eremin
Prof. Ernest Nazarian
Prof. Juan Alberto Montano
Prof. Esam Husein
Prof. Ivo Malakov
Prof. Krasimir Marchev
Prof. Leon Kukielka
Prof. Lyudmila Ryabicheva
Prof. Milan Vukcevic

Vice Chair: Prof. Dr. Eng. Tsanka Dikova

Prof. Mladen Velev
Prof. Mohamed El Mansori
Prof. Movlazade Vagif Zahid
Prof. Nikolay Dylgerov
Prof. Oana Dodun
Prof. Olga Krivtsova
Prof. Peter Kostal
Prof. Raul Turmanidze
Prof. Renato Goulart
Prof. Roumen Petrov
Prof. Sasho Guergov
Prof. Seiji Katayama
Prof. Sergej Dobatkin
Prof. Sergej Nikulin
Prof. Stefan Dimov
Prof. Svetan Ratchev
Prof. Svetlana Gubenko
Prof. Tale Geramitchioski
Prof. Vadim Kovtun
Prof. Viktor Vaganov
Prof. William Singhose
Prof. Yasar Pancar

BG
FR
AZ
BG
RO
KZ
SK
GE
BR
BE
BG
JP
RU
UK
UK
UA
MK
BY
RU
USA
TR

CONTENTS

MACHINES

UNDERWATER HULL OBSERVATION SYSTEM ARMUS Academician Stefan Vodenicharov, Professor Dr. Daniel Bratanov, Dr. Rumyana Mihaylova, Professor Kiril Stoychev, DSc, Eng. Valentin Najdenov	319
IMPACT OF PARAMETERS OF POWER TRANSMISSION SYSTEM STATE ON VEHICLE'S WORKING LIFE AND POWER EFFICIENCY Dr Eng. Damjanovic M., Ass. Prof. Dr Eng. Sibalic N., Prof. Dr Eng. Vukcevic M.	323
EVALUATION OF ENGINEERING SOLUTIONS IN WINE PRODUCTION Prof. Dr Eng. Vukcevic M., Ass. Prof. Dr Eng. Sibalic N., Dr Eng. Damjanovic M., Eng. Vaskovic N.	327
DESIGN AND OPTIMISATION OF 2DOF VEHICLE SUSPENSION SYSTEM Prof.Assoc. Dr. Ramiz Likaj, Prof.Assoc.Mirlind Bruci, Msc. Mehmet Qelaj	331
METHODS AND RESULTS OF EXPERIMENTAL RESEARCHES MACHINES FOR AUTOMATIC SORTING EGGS ON THE BASIS OF THE TECHNICAL VISION SYSTEM J. Alikhanov, Zh. Shynybay, A. Moldashanov, A. Kulimakhambetova, P. Daskalov	334
MATERIAL DEFORMATION ANALYSIS IN BRIDGE CRANE DURING TRAVEL MOTION WITH FULL LOADING Prof.assc. Bruci Mirlind, Prof.dr. Doçi Ilir, Prof.assc. Kyçyku Azem, Msc. Morina Blerim	338
RESEARCH AND ANALYSIS OF DYNAMIC PARAMETERS IN V-BELTS Azem Kyçyku, Nedaat Qehaja	342
FEM 2D AND 3D DESIGN OF TRANSFORMER FOR CORE LOSSES COMPUTATION Assoc. prof. Dr. Sarsic Vasilija	345
FLOTATION DEVICE WITH A HIGH FREQUENCY ROTARY PULSATION AERATOR (HFRPA) FOR ENRICHMENT OF FINE-GRADE GOLD-CONTAINING ORES Dr. Sci. (Eng.), Acad. NAS RoK Zhamanov A., Senior Researcher Khairullina S., Cand. Sci. (Eng.), Leading Researcher Berdikulova F., Senior Engineer Abdilmanapov N., Senior Engineer Sarsenbai A.	349
ANALYSIS AND MODELLING OF AUTOMOTIVE AIR FILTER AS A SUBSTITUTE FOR POWERCORE ITEM Assoc. Prof. Kandratsite Janusien R. PhD, Lect. Mateika D. PhD, Prof. Bulsuls A. Habil. PhD	354
FINITE ELEMENT ANALYSIS OF STRESS OF VEHICLES FRICTION CLUTCH DIAPHRAGM Ph.D. Simeon Simeonov, Ph.D. Petar Simonovski, Ph.D. Nikola Avramovski, Ph.D. Dejan Mirakovski, M.Sc. Saska Milev, Ph.D. Marija Cekirovska	358
ИВСЛЕДВАНЕ ВЛИЯНИЯТО НА ЗАМЪРСЯВАНЕТО НА ВЪЗДУШНИЯ ОХЛАДИТЕЛ И ИЗНОСВАНЕТО НА БУТАЛНИТЕ ПРЪСТЕНИ НА КОРАБНИТЕ ДВИГАТЕЛИ, ВЪРХУ СПЕЦИФИЧНИЯ РАЗХОД НА ГОРИВО, АЗОТНИТЕ И СЕРНИТИ ОКСИДИ ас. Христов, Д.Д.	363
ЕЛЕКТРОННО УСТРОЙСТВО ЗА РЕГИСТРИРАНЕ И ИЗМЕРВАНЕ НА СЛАБИ ИЗЛЪЧВАНИЯ В ДАЛЕЧНИЯ UV СПЕКТЪР НА МАГНИТОСФЕРАТА Инженер-физик Ташев В., Главен асистент Манев А.	367
ОРАЗМЕРЯВАНЕ НА ЗАДВИЖКАНЕ С ПОВИШЕНА МОЩНОСТ ПОСРЕДСТВОМ ВЕРНЖНА ПРЕДАВКА Assoc. Prof. Eng. Pandev Georgi, PhD	370
TSENTROBEZHNO'S DESIGN - THE GIRATSIONNY MILL WITH LOW CON-SUMPTION ELEKTROENERGY candidate of engineering sciences, associate professor Askarov E.S. , doc, PhD Arinova D.B., doc, PhD Zhankeldi A.Zh.	374
ANALYSIS OF KINEMATICS AND KINETOSTATICS OF FOUR-BAR LINKAGE MECHANISM BASED ON GIVEN PROGRAM Prof.Assoc. Dr. Shala A, Prof.Assoc.Dr. Likaj R., Prof.Ass. Dr. Bajrami X., MSc. Qelaj M.	377
THE STRESS VARIATION BY CHANGING THE SUPPORTING POINT LOCATION IN THE MOTOR VEHICLE CLUTCH ASSEMBLY M.Sc.Saska Milev, Ph.D. Simeon Simeonov, Ph.D. Petar Simonovski, Ph.D. Nikola Avramov, Ph.D. Saska Dimitrov, Ph.D. Slaveo Cvetkov	383
DESIGN PROCESS FOR THE SUSPENSION SYSTEM OF THE TERRAIN VEHICLE WITH FOUR WHEEL DRIVE Assoc. Prof. Dr. Naser Lajci, Assoc. Prof. Dr. Azem Kyçyku, Ass. Prof. Dr. Shpetim Lajci	388

ERGONOMICS & DESIGN

ПОТРЕБИТЕЛИ КАТО АВТОР гз. ас. д-р Маркова, К.	392
ОСНОВНИ МЕТОДИ ЗА ПРОЕКТИРАНЕ НА НАБОРНОТО ПОЛЕ НА СТРАНИЦАТА В КНИГА гз. ас. д-р Илиев, И.	395

THE STRESS VARIATION BY CHANGING THE SUPPORTING POINT LOCATION IN THE MOTOR VEHICLE CLUTCH ASSEMBLY

M.Sc. Sasho Milev^{1*}, Ph.D. Simson Simeonov^{1*}, Ph.D. Petar Simonovski^{2*}, Ph.D. Nikola Avramov^{2*}, Ph.D. Sasho Dimitrov^{1†}, and Ph.D. Slaveo Cvetkov^{1†}

^{1†} Faculty of Mechanical Engineering - Gocse Delcev University in Stip, Macedonia

^{2†} Faculty of Mechanical Engineering – Sa.Cyril and Methodius University in Skopje, Macedonia

E-mail: sasho.milev@ugd.edu.mk;

Abstract: The diaphragm spring as one of the most important parts of the motor vehicle clutch assembly provides the compressive force on the pressure disk. This force is needed for generating friction between the coupling of the flywheel and the pressure disk and transmitting the torque from the engine to the transmission. Therefore the diaphragm spring is subjected to complex loads. The nominal stress for dimensioning the spring is the tangential stress, which is calculated by the terms of Almen and Laszlo. The aim of this research is analyzing the location of the diaphragm spring supporting points of the clutch assembly and its effect on the caused stresses by using the Finite Element Method.

Keywords: DIAPHRAGM SPRING, FRICTION CLUTCH, EXPRESSIONS OF ALMEN AND LASZLO, TANGENTIAL STRESS

1. Introduction

The clutch coupling allows the engaging and disengaging of the vehicle transmission. The required compressive force for creating the friction necessary for torque transmission is achieved by the diaphragm spring. When performing its function, the diaphragm spring is subjected to dynamic loadings. The stresses occurring at the spring are compression and extension, figure 1. [1],[2].




Fig. 1 Spring stresses

The diaphragm spring used in the clutch assembly has the location of the supporting points as shown on the picture or in the case of a vehicle those are a supporting edges, figure 2.




Fig. 2 Diaphragm spring with its supporting points

By mounting the clutch in the vehicle, the shape of the spring changes, from its conical shape it becomes flat (it makes a deviation $f = h_0$), and then the process of spring loading starts. The spring has

two points of interest. Point 1 where the force F acts (created by the spring deflection) and the point 3 where the spring is supported, where the force is also equal to F . When the spring is in the flat position, the compression force allows the torque to be transmitted. Moving the release bearing for a certain path (deflection) causes the clutch to disconnect [3], [4].

2. Researching

The purpose of this research is by using the finite element method to determine the spring stress depending on the location of the supporting points in both the flat or mounted position and at the maximum deviation or disengaged position.

The analysis were carried out on a diaphragm spring for commercial vehicles with next dimensions : internal diameter of a diaphragm spring $D_i = 313$ [mm], outer diameter of a diaphragm spring $D_o = 395$ [mm], spring thickness $s = 5.2$ [mm], Module of elasticity of the steel $E = 206000$ [N/mm²], Poisson number of spring steel $\mu = 0.3$, internal diameter of the diaphragm spring with supporting points $D_{ap} = 336$ [mm], outer diameter of the diaphragm spring with supporting points $D_{ao} = 392$ [mm], path of the clutch while disengaging $f = 12$ [mm], release bearing diameter $d = 120$ [mm]. [5], [6]

Figures 3 and 4 shows the distribution of forces acting on the spring, with one and two supporting points used for the clutches.




Fig. 3 Spring with one supporting point




Fig. 4 Spring with two supporting points

In order to note the influence of the supporting points, the spring calculation was performed:

- supporting point A, by moving the spring from the initial or zero position to the flat position, the spring makes a deviation h_s .

The supporting point A is stationary, and the release bearing moves the spring from the flat position for the path ℓ that disengages the spring (maximum deviation is achieved).

- From the two supporting points A and B, in the flat position of the spring, the supporting point B is stationary. The release bearing moves from the flat position for the path ℓ_s , and the point A travels the distance f_s , and within this displacement the pressure disk is raised and the clutch is disengaged.

By using a Finite Elements Method (commercial software package), the spring cross-section is divided into 21 elements (Fig. 5) in which the stress is calculated. From the simulation results, the following diagrams for the tangential stress for two cases (Fig. 6 and 7) were obtained:

* The support point A is on a diameter of Ø392[mm], and the internal diameter $D_i = 313[\text{mm}]$ moves from the flat position to the flat position $f(h_s)$ and to a maximum deviation of f_{max} .

* The support point A is on a diameter of Ø392, and the supporting point B is on the diameter of Ø336[mm]. From the flat spring position, point B is stationary and point A moves in opposite direction from the direction of the release bearing that travels the distance ℓ , [7].




Fig. 5 FEM elements for stress calculation




Fig. 6 Diagram of tangential stresses with a support point A,




Fig. 7 Diagram of tangential stresses with two supporting points, A and B

Complex stresses are presented at figures 8 and 9 :





Fig. 8 Complex stress at the flat and disengaged position 0392/0






Fig. 9 Complex stress at the flat and disengaged position 0392/338

3. Analysis of the results and discussion :

The calculations were carried out by the FEM and the obtained diagrams (Fig. 6 and 7), for the change in the tangential stresses of the diaphragm spring body shown on the diagrams (Fig. 10 and 14) and the tables (1 and 2) were analyzed [4], [7].

Table 1: Tangential stresses at the spring flat position


393,0	392,0	390,2	381,3	369,5	358	346,2	334,5	322,7	315	D(mm)
8,86	8,75	8,55	7,57	6,27	5,0	3,7	2,4	1,1	0,22	Ø(mm)
1130		1130	1060	870	640	410	190	60	30	Ø392/336 σ(N/mm ²)
1170		1120	1055	870	645	410	230	80	35	Ø3920 σ(N/mm ²)



With one support _____, with two supports _____
Fig. 10 Distribution of the tangential stress at the flat position of the spring

Table 2: Tangential stresses at the spring disengaged position

393,0	392,0	390,2	381,3	369,5	358	346,2	334,5	322,7	315	D(mm)
2,8		3,2	3,7	4,3	5	5,6	6,5	8,13	9,8	Ø(mm)
120		370	500	620	540	570	740	1120	1280	Ø392/336 σ(N/mm ²)
12,35	12,23	12,0	10,57	8,77	7,0	5,15	3,33	1,51	0,28	Ø(mm)
885		920	1060	1020	850	575	300	110	50	Ø3920 σ(N/mm ²)



With one support _____, with two supports _____
Fig. 11 Distribution of the tangential stress at the disengaged position of the spring.

The highest tangential stress occurs in point 2 (if the supporting point is placed on the location of point 2), then it has the greatest deviation plus the deviation from the displacement of the release bearing traveling the distance of $\ell = 12\text{mm}$ ($\ell_{\text{max}} = 7.85 + 4.9 = 13.7\text{mm}$). This can be seen from the picture of the complex stress (Fig.12).




Fig.12 Complex stress at the disengaged position 0392/0313

4. Conclusion :

The following conclusions can be given:

- The stress at flat spring position with one and two supporting points has small deviation of one curve compared to the other.
- The stress at the maximum spring deflection has the mutual variation of the curves. With one support, the maximum stress occurs in the region of the point 3, and with two supports around the location of the point 2. The reason for this is that in the first case, the diaphragm spring is inclined like a beam fixed on one of its sides, and in the second case the spring is inclined on two supports.

References

- [1] Orthwein C. William: *Clutches and brakes : Design and Selection*. CRC Press, 2 edition (2004)
- [2] Nam W., Lee H., Choi Y.C. and Kwon D.J. *Finite Element Analysis and Optimal Design of Automobile Clutch Diaphragm Spring*. FISITA World Automotive Congress, Seoul, 2000-05-0125
- [3] Mubes Disc Spring Handbook. (1992). Catalogue.
- [4] Almen J.O. and Lasslo A. (1936). The Uniform-Section Disk Spring. (1936). *ASME* 58.
- [5] Kaya, N. Optimal design of an automotive diaphragm spring with fatigue resistance. *International Journal of Vehicle Design*. (2006) 126-43. Vol.40.
- [6] Nunney, Malcolm J. *Light and Heavy Vehicle Technology*. 4th ed. (2001) Elsevier Ltd, London.
- [7] Cook D. Robert *Finite Element Modeling for Stress Analysis*. Wiley, 1st edition (1995)